

Product Description

Electronic, 3 Conductor 20AWG (7x28) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-	10v,); low voltage control (24v,); line level audio; voic	e communications; panel wiring
onstruction Details			
onductor			
Element Number of Ele	nent Size Stranding Material		
Conductor(s) 3	20 AWG 7x28 TC - Tinned C	opper	
sulation			
Element Material	Nom. Thickness Nom. Insulation D	iameter Color Code	
Conductor(s) PE - Polyethyle	ne 0.017 in (0.43 mm) 0.070 in (1.8 mm)	Black, Red, Clear	
uter Shield			
Shield Type Materia	Coverage Drainwire Type		
Tape Bi-Laminate (Alu	im+Poly) 100% 20 AWG (7x28) TC		
uter Jacket			
Material Nor	n. Thickness Nom. Diameter		
PVC - Polyvinyl Chloride 0.03	3 in (0.84 mm) 0.218 in (5.54 mm)		
Overall Cable Diameter (Nomir	nal): 0.218 in (5.54 mm)		
lectrical Characterist	ics		
lectricals			
Element Nom. Conduct			Max. Current
	ft 27 pF/ft (89 pF/m)	51 pF/ft (170 pF/m)	8 Amps per Conductor at 30°C
Conductor(s) 11.1 Ohm/1000			
Conductor(s) 11.1 Ohm/1000			
oltage			
oltage UL Voltage Rating	093)		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Iechanical Characteri	093)		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Rechanical Characteri emperature	093) stics		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Iechanical Characteri	093) stics		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Acchanical Characteri emperature UL Temperature Operatin	093) stics		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Iechanical Characteri emperature JL Temperature Operatin 30°C -20°C to +6 end Radius	093) Stics 9 0°C		
oltage UL Voltage Rating 300 V (CM), 300 V (UL AWM 2 Acchanical Characteri emperature UL Temperature Operatin 30°C -20°C to +6 end Radius	9 9 0°C Win.		

Bulk Cable Weight:

28 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor			
Sustainability:	CA Prop 65			
Flammability / Reaction to Fire:	UL 1685 UL loading , FT1, IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca			
NEC / UL Compliance:	Article 800, CM			
AWM Compliance:	AWM 2093			
CEC / C(UL) Compliance:	СМ			
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

History

Update and Revision:

Revision Number: 0.490 Revision Date: 01-04-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN
8772.00152	Chrome	Reel	152 m	8719605019370
8772.00U152	Chrome	UnReel	152 m	8719605019394
8772.00305	Chrome	Reel	305 m	8719605019387
8772.00U305	Chrome	UnReel	305 m	8719605019400
8772 060500	Chrome	Reel	500 ft	612825215806
8772 060U500	Chrome	UnReel	500 ft	612825215783
8772 0601000	Chrome	Reel	1,000 ft	612825215790
8772 060U1000	Chrome	UnReel	1,000 ft	612825215776
8772 0605000	Chrome	Reel	5,000 ft	612825215813

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.