



Product: 9910 ☑

Lead Wire, #10 Str TC, PVC Ins, AWM 1015 AWM 1230

Request Sample

Product Description

Low Temp Plastic Lead Wire, 10AWG (65x28) Tinned Copper, PVC Insulation, AWM 1015 AWM 1230 CSA TYPE TEW JQA-F 600V 105C

Technical Specifications

Product Overview

Suitable Applications: inter-connection circuits, internal wiring of computer and electronic equipments, internal wiring of appliances, machine tool wire

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	1	10 AWG	65x28	TC - Tinned Copper

Insulation

Material	Nom. Thickness	Nom. Insulation Diameter
PVC - Polyvinyl Chloride	0.033 in (0.84 mm)	0.18 in (4.6 mm)
Overall Cable Diameter (I	Nominal): 0.18 in (4	.6 mm)

Electrical Characteristics

Electricals

Nom. Conductor DCR	Max. Current	
6.5 Ohm/1000ft	Single conductor in free air @ 30°C: 6.5 A	
Nom. Outer Shield DCR: 6 Ohm/km		

Voltage

UL Voltage Rating 600 V RMS

Mechanical Characteristics

Temperature

UL Temperature	Operating
105°C	-30°C To +105°C

Stationary Min. Installation Min.

Bend Radius

1.8 in (46 mm)	1.8 in (46 mm)
Max. Pull Tension:	:
Bulk Cable Weight	L.

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	VW-1, FT1

NEC / UL Compliance:	Article 310, MTW or TW
AWM Compliance:	AWM 1015, AWM 1230, CSA AWM I A/B
CEC / C(UL) Compliance:	TEW
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)

History

Update and Revision:	Revision Number: 0.442 Revision Date: 11-09-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
9910 010100	Black	Reel	100 ft	612825260790
9910 010250	Black	Reel	250 ft	612825260813
9910 0102000	Black	Reel	2,000 ft	612825260806
9910 002100	Red	Reel	100 ft	612825260714
9910 002250	Red	Reel	250 ft	612825260738
9910 0022000	Red	Reel	2,000 ft	612825260721
9910 009100	White	Reel	100 ft	612825260769
9910 009250	White	Reel	250 ft	612825260783
9910 0092000	White	Reel	2,000 ft	612825260776
9910 004100	Yellow	Reel	100 ft	612825260745
9910 004250	Yellow	Reel	250 ft	612825260752

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.