

Product Description

Low Temp Plastic Lead Wire, 20AWG (7x28) Tinned Copper, PVC Insulation, AWM 1007 AWM 1569 CSA TYPE TR-64 TRSR-64

Technical Specifications

Product Overview

Suitable Applie	cations:	inter-conn	ection circuits	s, internal wiring of con	puter and electronic equipments,	internal wiring of appliances	
Constructi	on Details						
onductor							
Element	Number of Elem	ent Size	Stranding	Material			
Conductor(s)	1	20 AWG	7x28	TC - Tinned Copper			
nsulation							
Mater				tion Diameter			
Mater	al Nom yl Chloride 0.016						

Electricals

Nom. Conductor DCR	Max. Current
11.2 Ohm/1000ft	Single conductor in free air @ 30°C: 11 A
Valtara	

Voltage

UL Voltage Rating	
300 V RMS	l

Mechanical Characteristics

UL Temperature	Operating	1
105°C -2	25°C To +105°C	
nd Radius		
Stationary Min. Ins	stallation Min	
0.69 in (18 mm) 0.6		
Max. Pull Tension:	1	1
Bulk Cable Weight:	Ę	5

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	VW-1, FT1
AWM Compliance:	AWM 1007, AWM 1569

CEC / C(UL) Compliance:	TRSR-64
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
History	

Update and Revision:

Revision Number: 0.486 Revision Date: 01-20-2023

Part Numbers

Variants				
Item #	Color	Putup Type	Length	UPC
9919 010100	Black	Reel	100 ft	612825262695
9919 0101000	Black	Reel	1,000 ft	612825262701
9919 013100	Blue, Dark	Reel	100 ft	612825262718
9919 0131000	Blue, Dark	Reel	1,000 ft	612825262725
9919 001100	Brown	Reel	100 ft	612825262558
9919 0011000	Brown	Reel	1,000 ft	612825262565
9919 0081000	Gray	Reel	1,000 ft	612825262664
9919 005100	Green, Dark	Reel	100 ft	612825262626
9919 0051000	Green, Dark	Reel	1,000 ft	612825262633
9919 0031000	Orange	Reel	1,000 ft	612825262596
9919 002100	Red	Reel	100 ft	612825262572
9919 0021000	Red	Reel	1,000 ft	612825262589
9919 007100	Violet	Reel	100 ft	612825262640
9919 0071000	Violet	Reel	1,000 ft	612825262657
9919 009100	White	Reel	100 ft	612825262671
9919 0091000	White	Reel	1,000 ft	612825262688
9919 004100	Yellow	Reel	100 ft	612825262602
9919 0041000	Yellow	Reel	1,000 ft	612825262619

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.