## **Detailed Specifications & Technical Data**



METRIC MEASUREMENT VERSION

ENTINGIAN CANAD

## 8500 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

For more Information please call







### **General Description:**

Tinned copper conductor, PVC insulation. Covers insulated wire for internal wiring of meters, panels, and electrical or electronic equipment. Temperatures to 105°C.

Physical Characteristics (Overall)	
Conductor AWG:	
# Conductors AWG Stranding Conductor Material	
1 16 19x29 TC - Tinned Copper	
Total Number of Conductors:	1
Insulation	
Insulation Material:	
Insulation Material Wall Thickness (mm)	
PVC - Polyvinyl Chloride 0.254	
Overall Insulation	
Overall Cable	0.007
Overall Nominal Diameter:	2.007 mm
Mechanical Characteristics (Overall)	
Bulk Cable Weight:	14.882 Kg/Km
Applicable Specifications and Agency Com	ppliance (Overall)
Applicable Standards & Environmental Program	
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-16878/1
MIL Spec Rating:	600 V, 105°C
Plenum/Non-Plenum	
Plenum (Y/N):	No

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8500 0011000	1,000 FT	10.000 LB	BROWN	Р	16 STR PVC BRN
8500 002100	100 FT	1.100 LB	RED		16 STR PVC RED

# **Detailed Specifications & Technical Data**



### METRIC MEASUREMENT VERSION

### 8500 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

8500 0021000	1,000 FT	10.000 LB	RED	P	16 STR PVC RED
8500 0031000	1,000 FT	10.000 LB	ORANGE	P	16 STR PVC ORG
8500 004100	100 FT	1.100 LB	YELLOW		16 STR PVC YEL
8500 0041000	1,000 FT	10.000 LB	YELLOW	P	16 STR PVC YEL
8500 005100	100 FT	1.100 LB	GREEN, DARK		16 STR PVC GRN
8500 0051000	1,000 FT	10.000 LB	GREEN, DARK	P	16 STR PVC GRN
8500 006100	100 FT	1.100 LB	BLUE, LIGHT		16 STR PVC LBLU
8500 0061000	1,000 FT	10.000 LB	BLUE, LIGHT	P	16 STR PVC LBLU
8500 0071000	1,000 FT	10.000 LB	VIOLET	P	16 STR PVC VIO
8500 0081000	1,000 FT	10.000 LB	GRAY	P	16 STR PVC GRY
8500 009100	100 FT	1.100 LB	WHITE		16 STR PVC WHT
8500 0091000	1,000 FT	10.000 LB	WHITE	P	16 STR PVC WHT
8500 010100	100 FT	1.100 LB	BLACK		16 STR PVC BLK
8500 0101000	1,000 FT	10.000 LB	BLACK	P	16 STR PVC BLK
8500 0151000	1,000 FT	10.000 LB	WHITE/RED	A	16 STR PVC WHT/RED
8500 0161000	1,000 FT	10.000 LB	WHITE/GREEN	A	16 STR PVC WHT/GRN
8500 0171000	1,000 FT	10.000 LB	WHITE/YELLOW	A	16 STR PVC WHT/YEL
8500 0181000	1,000 FT	10.000 LB	WHITE/BLUE	A	16 STR PVC WHT/BLU
8500 0191000	1,000 FT	10.000 LB	WHITE/BROWN	A	16 STR PVC WHT/BRN
8500 0201000	1,000 FT	10.000 LB	WHITE/ORANGE	A	16 STR PVC WHT/ORG

#### Notes:

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 11-07-2014

© 2019 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).